

**CHARACTER:**

**1.Physical performance**

- a、Excellent mechanical properties
- b、Excellent thermal stability
- c、Low temperature soft good performance
- d、Good flame retardancy
- e、high of resistance to chemicals
- f、Chemistry stability is good

**2.Electrical Properties**

- a、Electrical insulation good
- b、Good the dielectric properties

**3.Processing properties**

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、According to UL standard design

**4.Environmental protection**

- a、low smoke, non-halogen
- b、ROHS/REACH compliant


**SHOULD BE USED:**

Motor Leads or Internal Wiring of Appliances.

**REFERENCE:**

UL758-2010、UL1581-2009

**Outline:**



**Wire structure description:**  
 Conductor: Tinned /Bare copper ;  
 Insulation materials: XLPE Insulation

Internal wiring of Appliances. Conductor temperature not over150℃ XLPE insulated wire  
 Rated temperature: 150℃ rated voltage: 600V

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20℃ (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Nom.	Tole.
3288	10	105/0.254	3.54	3.00	0.80	0.69	4.60	±0.15
	12	65/0.254	5.64	2.42	0.80	0.69	3.95	±0.15
	14	41/0.254	8.96	1.92	0.80	0.69	3.45	±0.15
	16	26/0.254	14.60	1.50	0.80	0.69	3.10	±0.1
	18	16/0.254	23.20	1.18	0.80	0.69	2.75	±0.1
	20	21/0.18	36.70	0.95	0.80	0.69	2.55	±0.1
	22	17/0.16	59.40	0.76	0.80	0.69	2.35	±0.1
	24	11/0.16	94.20	0.61	0.80	0.69	2.20	±0.1
	26	7/0.16	150.00	0.48	0.80	0.69	2.08	±0.1
	28	7/0.127	239.00	0.38	0.80	0.69	1.98	±0.1
	30	7/0.10	381.00	0.30	0.80	0.69	1.90	±0.10

**Marking:** E211048 AWM STYLE 3288 NO.AWG 150℃ 600V XLPE QIFURUI   
 AWM I A 150℃ 600V FT2 -LF-  
 E211048 AWM STYLE 3288 NO.AWG150℃ 600V VW-1 XLPE QIFURUI   
 AWM I A 150℃ 600V FT1 -LF-  
 OR: E211048 AWM STYLE 3288 NO. AWG 150℃ 600V XLPE QIFURUI 221756  
 CSA AWM I A 150℃ 600V FT2 -LF-

**SAE COLOR SERIES**

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

**PACKAGE**

*PACKAGE					
Part No.	Packing- FT/roll				
10AWG	<input type="checkbox"/> 200Ft	<input checked="" type="checkbox"/> 500Ft	<input type="checkbox"/> 1000Ft	<input type="checkbox"/> 2000Ft	
12~16AWG	<input type="checkbox"/> 200Ft	<input type="checkbox"/> 500Ft	<input checked="" type="checkbox"/> 1000Ft	<input type="checkbox"/> 2000Ft	
18~30AWG	<input type="checkbox"/> 200Ft	<input type="checkbox"/> 500Ft	<input type="checkbox"/> 1000Ft	<input checked="" type="checkbox"/> 2000Ft	

According to customer requirements for packaging packaging